

Items Supplied >

1 – Sissy Bar Rack

Application >

KAWASAKI VULCAN 800B 95-05

Instruction Manual >

02-3503

1. Working on the right hand side of the motorcycle, remove the two bolts, which secure the sissy bar to the support bracket. Set the bolts aside for reassembly.
2. Carefully slide the sissy bar rack between the support bracket and sissy bar, aligning the holes.
3. Install the bolts removed in Step 1 and finger tighten.
4. Repeat steps 1 through 3 on the left hand side of the motorcycle.
5. Tighten bolts to 12 ft. lbs.

*** Cobra sissy bar racks are designed to fit with Cobra sissy bars only ***

*** Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.**

04/01

Anything's Possible.

Items Supplied >

1 – Sissy Bar Rack

Application >

KAWASAKI VULCAN 800B 95-05

Instruction Manual >

02-3503

1. Working on the right hand side of the motorcycle, remove the two bolts, which secure the sissy bar to the support bracket. Set the bolts aside for reassembly.
2. Carefully slide the sissy bar rack between the support bracket and sissy bar, aligning the holes.
3. Install the bolts removed in Step 1 and finger tighten.
4. Repeat steps 1 through 3 on the left hand side of the motorcycle.
5. Tighten bolts to 12 ft. lbs.

*** Cobra sissy bar racks are designed to fit with Cobra sissy bars only ***

*** Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.**

04/01

Anything's Possible.