

Items Supplied >

- 1 - Sissy Bar w/pad
- 2 - Brackets
- 4 - 8mm x 16mm Button head Bolts
- 4 - 8mm x 40mm Button head Bolts

Application(s) >

INTRUDER 1500 98-02

Instruction Manual >

02-4830/02-5330/02-5830

Your sissy bar will install in just a few minutes using common tools. Read all instructions carefully and completely before installing your new sissy bar.

1. Remove the two (2) rear bolts on each fender rail.
2. Install the brackets with the bent portion toward the inside using the supplied 8mm x 40mm bolts and tighten. Brackets will mount on the outside of fender rail.
3. Install the sissy bar to the brackets using the supplied 8mm x 16mm bolts and tighten.

** Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.*

DOCUMENT NO. 0019 REV. A
04/01

Anything's Possible.

Items Supplied >

- 1 - Sissy Bar w/pad
- 2 - Brackets
- 4 - 8mm x 16mm Button head Bolts
- 4 - 8mm x 40mm Button head Bolts

Application(s) >

INTRUDER 1500 98-02

Instruction Manual >

02-4830/02-5330/02-5830

Your sissy bar will install in just a few minutes using common tools. Read all instructions carefully and completely before installing your new sissy bar.

1. Remove the two (2) rear bolts on each fender rail.
2. Install the brackets with the bent portion toward the inside using the supplied 8mm x 40mm bolts and tighten. Brackets will mount on the outside of fender rail.
3. Install the sissy bar to the brackets using the supplied 8mm x 16mm bolts and tighten.

** Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.*

DOCUMENT NO. 0019 REV. A
04/01

Anything's Possible.