MOUNTING INSTRUCTIONS

2321-0242 SPORTSHIELD PLATE ONLY YAMAHA 1300 V-STAR DETACHABLE, BLACK

⚠ WARNING

Read and follow these directions carefully.
During installation, make sure that the windshield and hardware do not interfere with any cables or wiring when the forks are turned all the way in either direction. Also make sure, through the full range of adjustment, that the windshield and hardware do not hit the tank.

This is a detachable windshield, *ALWAYS* make sure the Locking Mechanism is Fully Engaged after installing the windshield!
The improper installation of this kit and related components could result in serious injury or death.

1.**Cover gas tank and front fender with towels to avoid damage during installation.**

2. Install the windshield mounting plates onto the windshield, using the bolts that are pre-assembled on the mounting plates. The Santoprene grommets should be inserted through the holes in the windshield so that the flat round part lies flat on each side of the plastic. *NOTE: Tabs will point in towards headlight when properly installed.* (see Figure 1)
3. Install the windshield by placing the lower slots into the lower mounting bushings. Slip the upper slots into the upper mounting bushings and gently but firmly seat the slots into place. Lock the locking mechanism into place. (see figure 2 and 3)
4. Tighten all mounting bolts. Adjust the height, angle and alignment of the windshield and tighten ***ALL*** bolts. (See figure 4)

Note: This is a detachable windshield, *ALWAYS* make sure the Locking Mechanism is Fully Engaged after installing the windshield! (see figure 3)

CAUTION

IMPORTANT CARE AND CLEANING INSTRUCTIONS

Memphis Shades Windshields and Lowers are made of Lucite® acrylic, and will last for years with proper care. Clean your windshield with plenty of soapy water — mild dishwashing liquid is best — and a soft cotton cloth. Use your bare hand to feel and dislodge bugs, or cover with a wet soapy towel and let it soak. Don't use paper towels and don't scrape with anything. Small scratches can be removed with NOVUS # 2.

NEVER use any glass cleaning products, petroleum based chemicals, or cleaning agents with ammonia, bleach or any other harsh chemicals. This includes (but not limited to) RainX, brake fluid, acetone, paint thinner, benzene and gasoline. "If it hurts your nose, it will hurt the plastic."

Glass cleansing agents will cause severe damage to your windshield, and will void your warranty.

NOTE: At certain times of the day the Sunlight can reflect off the curvature of a windshield and cause extreme heat build-up on motorcycle instruments and instrument panel. Take care when parking. Park facing the sun, place an opaque object over the instruments or adjust the windshield to avoid reflections.



Figure 1

Figure 2

MOUNTING INSTRUCTIONS

2321-0242 SPORTSHIELD PLATE ONLY YAMAHA 1300 V-STAR DETACHABLE, BLACK

PART #	DESCRIPTION	QTY.
M8821	MOUNTING INSTRUCTIONS	1
M1139EB	LEFT SPORTS PLATE, BLACK	1
M1140EB	RIGHT SPORTS PLATE, BLACK	1
R322C	CLUTCH SIDE LATCH ASSEMBLY	1
R322T	THROTTLE SIDE LATCH ASSEMBLY	1
R334	6-32 X 3/8" FLAT HEAD SS SCREW	8
R326	SS SPRING	2

PART #	DESCRIPTION	QTY.
M543	SANTOPRENE GROMMET	4
M504EB	SOCKET SHOULDER WASHER, BLACK	4
M302	1/4"-20 X 1/2" SOCKET HEAD CAP SCREW	4
M505EB	BUTTON NUT, BLACK	4

Figure 3



1. M1140EB
2. M1139EB



1. Place lower slot into lower bushing. 2. Rotate top slot into place. 3. & 4. Secure locking Mechanism.

R322C/T LATCH ASSEMBLY



NOT CORRECT

CORRECT
Fully engaged Locking mechanism

Figure 4



Loosen Allen Bolt to adjust angle, then re-tighten Allen Bolt.

Memphis Shades warrants all product components, metal and plastic, against defects in materials and workmanship for 24 months.

FOR PARTS AND WARRANTY HELP, CONTACT:
MEMPHIS SHADES
P. O. Box 429
Rossville, TN 38066
(901) 853-0293
Visit us on the web at www.memphisshades.com or
you can also reach us at
customerservice@memphisshades.com