

**MEM-9846 MOUNTING KIT
SUZUKI VS1500 LC INTRUDER SPORTSHIELD**

TOOLS REQUIRED:

- (1) Towel
- (1) Phillips head screwdriver
- (1) 4mm Allen wrench
- (1) 7/16" or 11mm Wrench

1. Cover the front fender with a towel, just in case you drop something on it.
2. Remove the headlight lens by extracting the two Phillips head screws located on the sides of the headlight housing. Set it aside for later re-installation.
3. Remove the turnsignal bar using a 5MM Allen Wrench, remove the two allen head screws located between the forks on the underside of the bar and the third bolt located just under the headlight (use the hole in the bottom of the headlight housing to get to the third bolt)
4. Let the turnsignal bar hang gently while you install the brackets.
5. Remove the four bolts on the front of the fork covers, there are two located on the fork covers above the headlight, and two behind the turnsignal bar that was just removed.
6. Install the mounting brackets using the original bolts. Place one black spacer washer at the top between the bracket and the motorcycle.
7. Re-install the turnsignal bar and headlight lens and loosen the four mounting points on the sides of the brackets to receive the windshield.
8. Install the mounting plates on the windshield using the bolts that are pre-assembled on the mounting plates. The rubber grommets should be inserted through the holes in the windshield so that the flat round washer part of the grommet lays flat on each side of the windshield. On each plate, get both tabs started before you tighten either. The mounting tabs should be pointing out towards the edges of the windshield when installed properly.
9. Mount the windshield onto the brackets and adjust the angle and height and tighten all mounting bolts.

NEVER RIDE WITH ANY HARDWARE MISSING OR LOOSE, CONTACT MEMPHIS SHADES FOR FREE REPLACEMENT PARTS.

Care and Cleaning Instructions

To clean your windshield, use only warm water and a mild non-abrasive, dishwashing liquid. Use a soft cloth, such as a T-shirt or flannel cloth. To protect your windshield, please use Novus #2 to remove minor scratches, or use a polish like Memphis Shades Shinola which is specially designed for plastic windshields; glass cleansing agents will cause severe damage to your windshield and will void your warranty.

Never use any glass products, petroleum based chemicals, or cleaning agents with ammonia, bleach or any harsh chemicals. This includes Rain-X, brake fluid, acetone, and gasoline.

**MEM-9846 MOUNTING KIT
SUZUKI VS1500 LC INTRUDER SPORTSHIELD**

PART#	DESCRIPTION	QTY.
M846	MOUNTING INST/PARTS LIST	1
M787	LEFT MOUNTING PLATE	1
M788	RIGHT MOUNTING PLATE	1
M505	BUTTON NUT	4
M302	1/4"- 20 X 1/2" SS SOCKET HEAD CAP SCREW	4
M504	SOCKET SHOULDER WASHER	4
M543	SANTOPRENE GROMMET	4

**Memphis Shades warrants all product components, metal and plastic,
against defects in materials and workmanship for 24 months.**

FOR PARTS AND WARRANTY HELP, CONTACT:

MEMPHIS SHADES

P.O. Box 429

Rossville, TN 38066

(901) 853-0293

Visit us on the web at www.memphisshades.com or

you can also reach us at

customerservice@memphisshades.com

MEM9846 01-03-08