



# MOUNTING INSTRUCTIONS



## MEM-9908 FATS/SLIMS MOUNTING KIT \*WIDE

### ⚠ WARNING

Read and follow these directions carefully. During installation, make certain that when turning the forks, there can be no interference with wiring or cables **AND**, that the windshield can not hit the gas tank, through the windshield's full range of adjustment.

This is a quick change kit, **ALWAYS** tighten all mounting bolts after removing or installing the windshield!

The improper installation of this kit and related components could result in serious injury or death.

Additional tools required that are not included in this kit. 7/16" or 11mm Wrench.

1. Cover gas tank and front fender with towels to avoid damage during installation.
2. Install the two mounting plates onto the windshield, using the bottom and third bolt up. Leave the nylon washers off. The small tab goes to the bottom, big one at the top. *Tabs point out towards the edge of the windshield.* (see fig. 1)
3. Loosely install the four Fork Clamps on the forks, approximately 2" apart. (see figure 2)
4. Loosen the four anchor bolts that are to hold the windshield to the Fork Clamps, and slip the windshield mounting plates and windshield onto the fork clamps. (see figure 3)
5. Adjust the height, angle and alignment of the windshield and tighten **ALL** bolts.

**Note:** This is a quick change kit, **ALWAYS** tighten all mounting bolts after removing or installing the windshield!

### CAUTION

#### IMPORTANT CARE AND CLEANING INSTRUCTIONS

Memphis Shades Windshields and Loweres are made of Lucite® acrylic, and will last for years with proper care. Clean your windshield with plenty of soapy water — mild dishwashing liquid is best — and a soft cotton cloth. Use your bare hand to feel and dislodge bugs, or cover with a wet soapy towel and let it soak. Don't use paper towels and don't scrape with anything. Small scratches can be removed with NOVUS # 2.

**NEVER** use any glass cleaning products, petroleum based chemicals, or cleaning agents with ammonia, bleach or any other harsh chemicals. This includes (but not limited to) RainX, brake fluid, acetone, paint thinner, benzene and gasoline. "If it hurts your nose, it will hurt the plastic."

**Glass cleansing agents will cause severe damage to your windshield, and will void your warranty.**

**NOTE:** At certain times of the day the Sunlight can reflect off the curvature of a windshield and cause extreme heat build-up on motorcycle instruments and instrument panel. Take care when parking. Park facing the sun, place an opaque object over the instruments or adjust the windshield to avoid reflections.




Fig. 1




Fig. 2




Fig. 3




# MOUNTING INSTRUCTIONS



## MEM-9908 FATS /SLIMS MOUNTING KIT \*WIDE

PART #	DESCRIPTION	QTY.
M908	MOUNTING INSTRUCTIONS/PARTS LIST	1
M596	LEFT MOUNTING PLATE FATS/SLIMS	1
M597	RIGHT MOUNTING PLATE FATS/SLIMS	1
M301	1/4" - 20 X 3/8" SOCKET HEAD CAP SCREW	4
M302	1/4" - 20 X 1/2" SOCKET HEAD CAP SCREW	4
M501	BEVELED SOCKET WASHER	4
M561	1/4" X 3/4" BEVELED SPACER WASHER	4

PART #	DESCRIPTION	QTY.
M520	INNER ADJ. FORK CLAMP HALF	4
M521	OUTER ADJ. FORKCLAMP HALF	4
M306	1/4" - 20 X 5/8" SS SOCKET HEAD CAP SCREW	4
M310	3/16" SHORT ARM ALLEN WRENCH	1
M313	3/16" ALLEN WRENCH COVER	1
M314	3/16" T-HANDLE ALLEN WRENCH	1
M337	3/16" T-HANDLE ALLEN WRENCH COVER	1



Memphis Shades warrants all product components, metal and plastic, against defects in materials and workmanship for 24 months.

**FOR PARTS AND WARRANTY HELP, CONTACT:**

MEMPHIS SHADES

P. O. Box 429

Rossville, TN 38066

(901) 853-0293

Visit us on the web at [www.memphisshades.com](http://www.memphisshades.com) or

you can also reach us by email:

[customerservice@memphisshades.com](mailto:customerservice@memphisshades.com)